Thunderbird e-pasta konfigurācija

Saturs

levads	2
Jaunākās Thunderbird versijas iegūšana	2
Lai veiktu Thunderbird e-pasta konfigurāciju	
Thunderbird opciju logs	11
Vēstuļu piegādes iestatījumi	12
Konta iestatījumu logs	13
Izejošā servera (SMTP) iestatījumu izvēle	14

levads

Latvijas Universitātes IT departaments LU darbinieku e-pastu nodrošina ar sistēmu Office 365, līdz ar to LU darbiniekiem tiek ieteikts lietot tiešsaistes (online) Outlook e-pastu <u>https://outlook.office.com/</u> vai Outlook standalone e-pasta klientu datorā vai mobilajā ierīcē. Tiem darbiniekiem, kas līdz šim lietoja Thunderbird e-pastu savā datorā, un būs vēlme lietot to arī turpmāk, obligāti būs jāveic Thunderbird e-pasta klienta atjaunināšana uz jaunāko versiju un pārkonfigurācija.

Jaunākās Thunderbird versijas iegūšana

Pats vienkāršākais veids ir doties uz lietotnes izstrādātāju mājas lapu un lejupielādēt pēdējo versiju: <u>https://www.thunderbird.net/en-US/</u>

Lejupielādējot un palaižot šo failu, jāpiekrīt sistēmas drošības paziņojumam par jaunas programmatūras darbināšanu uz jūsu iekārtas. Pēc tam sākas pats uzstādīšanas process, poga **"Tālāk (Next)"**:



Ja neesat droši, iesakām izvēlēties uzstādīšanu pēc noklusējuma **"Standart"**, un tālāk noklikšķinot uz pogas **"Tālāk (Next)"**:



Ja nepieciešams, var mainīt instalācijas atrašānās vietu pēc noklusējuma, un ieteicams izvēlēties, ka Thunderbird būs noklusētais e-pasta klients, poga **"Instalēt (Install)"**:

Mozilla Thunderbird Setup			×
Summary			1.
Ready to start installing Thunderbird			
Thunderbird will be installed to the following l	ocation:		
C:\Program Files\Mozilla Thunderbird			
Click Install to continue.			
	< Back	Install	Cancel

Notiek uzstādīšanas process, kura beigās piedāvā atvērt programmu sākotnējai konfigurēšanai, poga "Pabeigt (Finish)":



Pēc tam nepieciešams veikt pirmreizējo iestatīšanu, norādot Vārdu, Uzvārdu un LU e-pasta kontu, un noklikšķinot uz pogas **"Turpināt (Continue)"**:

×	Home	🛛 Account Setup	×	J		-	
8							
	Set Up Your E	xisting Email A	ddres	S			
Ø	To use your current email	address fill in your creden	tials.				
Q	Thunderbird will automat	ically search for a working a	and recomm	ended server configuration.			
	Your full name						
	Jānis Paraudziņš			()			
	Email address				08		
	janis.paraudzins@lu.lv			0	No 38		
	Password				3 21		
	•••••			ø	27 K		
	Remember password				Sol (Colo		
	Configure manually	Canc	el Co	ntinue	00		
	Your credentials will only be	stored locally on your compu	ter.				

Sistēma pārbaudīs, un piedāvās izvēlēties vienu no veidiem, kā pieslēdzamies Microsoft O365. Nepieciešams izvēlēties **IMAP** un pēc tam pielabot iestatījumus manuāli **"Uzstādīt manuāli (Configure manually)"**:

\boxtimes	Home	🔀 Account Setup	×	-
A				
	Set Up Yo	our Existing Email Ad	ddress	
0	To use your curre Thunderbird will a	nt email address fill in your credentia utomatically search for a working ar	als. Id recommended server c	onfiguration.
	Your full name			
	Jānis Paraudziņš		0	
	Email address			
	janis.paraudzins@	lu.lv	0	
	Password			
	•••••		ø	
	🗸 Remember pas	sword		
	🗸 Configuratio	on found in Mozilla ISP database.		
	Available configu	urations		Not sure what to select?
	_			Setup documentation - Support forum - Privacy policy
	IMAP Keep your f	olders and emails synced on your se	nver	
			i ver	
	outlook.	office365.com		
	Coutgoin	g SMTP STARTTLS		
	& Usernan	ie		
	janis.para	audzins@lu.lv		
	Keep your f	olders and emails on your computer		
	Exchange/C	Office365		
	Use the Mic	roson Exchange server or Office365	cioud services	
	Configure manually	Cancel	Done	
	configure manually	Cancer	Done	
	Your credentials wil	only be stored locally on your compute	r.	

Turpinam uzstādīšanu manuāli. Pārliecinies, ka visos laukos ir iestatītas pareizās vērtības, ka autentifikācijas metode ir pareizi iestatīta kā Oauth2, nevis kāda cita, un ka norādīts pareizais lietotājvārds (logins@edu.lu.lv). Ja viss pareizi, poga **"Gatavs (Done)".**

	Home	🛛 Account Setup	×		-
A					
	Set Up Your Ex	kisting Email Addı	ress		
2 2	To use your current email a Thunderbird will automatic	ddress fill in your credentials. ally search for a working and rea	commended server confi	figuration.	
	Jānis Paraudziņš		0		
	janis.paraudzins@lu.lv		0	•• •••	
	Password		ø		
	Remember password				
	✓ Configuration found	in Mozilla ISP database.			
	Manual configuration			Not sure what to select?	
				Setup documentation - Support forum - Privacy po	licy
	Protocol:	IMAP	~		
	Hostname:	outlook.office365.com			
	Port:	993			
	Connection security:	SSL/TLS	\sim		
	Authentication method:	OAuth2	~		
	Username:	janis.paraudzins@lu.lv			
	OUTGOING SERVER				
	Hostname:	smtp.office365.com			
	Port:	587			
	Connection security:	STARTTLS	~		
	Authentication method:	OAuth2	~		
	Username:	janis.paraudzins@lu.lv			
		Ad	lvanced config		
	Re-test	Cancel	Done		
	Thunderbird will attempt to a	to-detect fields that are left blank.			
	Your credentials will only be st	ored locally on your computer.			

Tālāk sistēma pārbaudīs Jūsu autorizāciju Outlook serveros. Ievadām paroli, un nākamajā ekrānā apstiprinām divfaktoru autentifikāciju. Ievadām paroli, poga "Pierakstīties (Sign In)".

	Home	📴 Account Setup	×		-		\times					
A												
	Set l	Jp Your Existing Email A	ddress									
Ø	To use y	our current email address fill in your credent	ials.									
Q	Thunderbird will automatically search for a working and recommended server configuration.											
	Jānis Pa	name iraudzīnš	0									
	Email add	Email address										
		Enter credentials for janpar@edu.lu.lv on outlook.	ptricesop.com									
	Passwo	https://login.microsoftonline.com/common/	oauth2/v2.0/authorize?response	_type=code&client_id=08162f7c-0fd2-420)-a84a-f25a4db0b584&rec	lirect_uri	=http%3A					
	Ret											
	Manus											
	INCO											
	Prote											
	FIOR		Microsoft									
	Host		janpar@edu.lu.lv									
	Port:		Enter passv	vord								
	Conn											
	Auth											
	- auti		Forgot my password									
	Useri		Sign in with another	account								
	оит			Sign in								
	Host			Jan								
	Port											
	Porc											
	Conn											
	Autho											
	User											
					Terms of	use P	rivacy & co					
	Re-te	Cance	Done									

Nākamajā ekrānā apstiprinam divfaktoru autentifikāciju.

	ł	Home	👰 Account Setup	×	:				-		×
A											
		Set Up Your	Existing Email A	Addre	SS						
9		To use your current em	ail address fill in your creden	itials.							
Q		Thunderbird will automa	atically search for a working	and recor	nmended se	erver configuration.					
		Your full name									
	6	Fata and attick for income	adu lu huan authach affina265 a		0						
	1	A https://login.missocofte	elias sem (semmen (lasia	om							
	4	nttps://iogin.microsofto	niine.com/common/iogin								
				Micro	osoft						
			ja	npar@eo	lu.lu.lv	1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.					
			Α	ppro	ve sig	n in reques	t				
			6	Open	your Mic	rosoft Authenticate	or app and				
				appro	ove the re	quest to sign in.					
				Don't	ask again	for 30 days					
			1 c	can't use	my Microso	oft Authenticator app	right now				
			M	lore infor	mation						
								_			
							_	Terms of use	Privacy	& cookies	;
				Advar	nced config						
		Re-test	Canc	el	Done						
		Thunderbird will attempt t	to auto-detect fields that are left	t blank.							
		Your credentials will only I	be stored locally on your compu	iter.							
Ŕ											
l←	(tex)										
-	(10)										

Nākamajā solī mums ir jāpiekrīt noteikumiem, ar kādiem Thunderbird lietotne drīkst pieslēgties LU outlook serveriem, poga **"Pieņemt (Accept)"**:



Jūsu konts veiksmīgi ir izveidots, poga "Pabeigt (Finish)".

D Inbox	🖂 Ac	count Setup	×	
✓ ACCOU You can now u You can impro	UNT SUCCESSF se this account with TI ve the experience by (fully creat hunderbird. connecting related	ed d services a	and con
😭 janis.pa	araudzins@lu.lv			IMAP
🇱 AC	count settings dd a signature	 mo End-to-end 	encryptior dictionaries	5
Connect ye	our linked servic	es		
Setup other serv	rices to get the most out	of your Thunderbir	rd experienc	e.
🛃 Conn	ect to a CardDAV add	ress book		
🛃 Conn	ect to an LDAP addres	ss book		
🛱 Conn	ect to a remote calenc	dar		
	Fir	nish		

------ beidzas jaunā daļa -----

1. Atveriet Thunderbird aplikāciju, noklikšķiniet uz sadaļas "lestatījumi (Settings).

🔽 🖂 janis nara	audzins@lu.lv					- 1		×	
				O Court (Chile K)				_	
A Get Messa	ages 🗸 🖉 write	♥ lag ♥ 1M Quick Filter		>> Search < Ctri+K>				=	
Folders		ianis.paraudzins @lu	u.lv			Account S	ettinge		
	@lu.lv (* 9347)	jamaiparatazina (e.i.				B) ACCOUNTS	eungs		
- Cocal F	olders								
💬 🔟 Irash	ox	Read messages							
<u> </u>		(a) Near messages	₽ white a new message	- Search messages in m	anage message mers				
		End-to-end Encryptic	on						
		Set Up Another Acco	unt						
		🖂 Email	🛅 Calendar	🙉 Address Book	荣 Chat				
Setti	ngs				2				
lesta	tījumi	🔗 Filelink	Feeds	Newsgroups					
10500									
		Import from Another Program							
-		Thunderbird lets you imp filters from other mail pro	ort mail messages, address ograms and common addr	s book entries, feed subscriptions, set ess book formats.	tings, and/or				
\$			- <u>-</u>						
(← ((a)) inpis par	udzing@lu.ly. Download	ing massage 201 of 27052 in In	hav						

2. Tālāk noklikšķiniet uz sadaļas "Konta iestatījumi (Account Settings)":

×	🛯 janis.paraudzins@lu.lv	to Settings X	- 🗆 🛛
8 1		₽ Find in Sett	ings
Ø	ිලි General	General	
**	🖉 Composition	Thunderbird Start Page	
	Privacy & Security	✓ When Thunderbird launches, show the Start Page in the message area	<u>R</u> estore Default
	💬 Chat		
		G Google ✓ Add Remove	
感	Account Settings Add-ons and Themes	System Integration Always check to see if Thunderbird is the default mail client on startup When Thunderbird is minimized, move it to the tray Allow Windows Search to search messages	Check <u>N</u> ow
. I←	(••) janis.paraudzins@lu.lv Downlo	ading message 2321 of 27952 in Inbox	-

3. Noklikšķiniet uz sadaļas Return Receipts... .



Thunderbird opciju logs

Izvēlamies opciju Never send a return receipt, un apstipriniet izmaiņas, noklikšķiniet uz pogas "Labi (OK).

Return Receipts									
When sending messages, always request a return receipt									
When a receipt arrives:	When a receipt arrives:								
O Leave <u>i</u> t in my Inbox									
O Move it to <u>my</u> "Sent" folder									
When I receive a request for a return receipt:									
 Allow return receipts for some messages 									
I <u>f</u> I'm not in the To or Cc of the message:	Ask me	\sim							
If <u>t</u> he sender is outside my domain:	Ask me	\sim							
In <u>a</u> ll other cases:	Ask me	\sim							
	ОК	Cancel							

Vēstuļu piegādes iestatījumi

Atlasiet sadaļu "Servera iestatījumi (Server Settings)", un salīdziniet attēlā redzamo nepieciešamo informāciju (servera un drošības iestatījumus). Parametriem ir jābūt tā kā ir norādīts attēlā. Servera adrese ir outlook.office365.com, ports ir 993, protokols ir SSL/TLS un autentifikācijas protokols OAuth2.

Advanced...

 \times

3va	r <mark>īgi!</mark> Ja izmantojiet IMAI	P servera tip	ı, tad	porta numurs ir	993.	
	 janis.paraudzins@lu.lv ianis.paraudzins@lu.lv Server Settings Copies & Folders Composition & Addressing Junk Settings Synchronization & Storage End-To-End Encryption Return Receipts Local Folders Junk Settings 	3 Settings Server Setti Server Type: IN Server Name User <u>N</u> ame: Security Settin Connection sec	X NGS 1AP Mail S outlook.of anpar@ed ngs grity:	Account Settings Account Settings University Account Settings SSL/TLS Outplay Account Settings Account Sett	×	
	Disk Space	Server Setting	js w messag w messag diate serve	ies at startup ies every 10 💭 min ir notifications when new m	utes essages arrive	

🗑 Trash on aivars.liepa@lu.lv 🗸

When I delete a message:

O Move it to this folder: Just mark it as deleted Remove it immediately

Konta iestatījumu logs

Tālāk ir jānokonfigurē izejošā servera (SMTP) iestatījumi, atlasiet konta iestatījumu logā **Outgoing Server** (SMTP)

\bowtie	🔀 janis.paraudzins@lu.lv	鏱	Settings	×	Account Settings		×		-		×
	「読 janis.paraudzins@lu.lv Server Settings Copies & Folders Composition & Addressing		Outgoing Server (SMTP) Settings When managing your identities you can use a server from this list by selecting it as the Outgoing Server (SMT can use the default server from this list by selecting "Use Default Server".						ſ₽), or yc	u	
予 ②	Junk Settings Synchronization & Storage End-To-End Encryption Return Receipts ✓ ➡ Local Folders Junk Settings Disk Space Colleging Server (SMTP) Account Actions ✓ Account Actions ✓ Add-ons and Themes (a) Local polytopic Settings		Office365	selected serve Description: C Server Name: ja Vort: 5 User Name: ja tion method: C tion Security: S	er: 2)ffice365.com (D) er: 2)ffice365 (Microsoft) mtp.office365.com 87 anpar@edu.lv 2)Auth2 .TARTTLS	lefault)			F	Add	

Salīdzinam redzamos datus ar paraugu. Serveris ir **smtp.office365.com**, ports **587**, protokols **STARTTLS** un autentifikācijas metode OAuth2. Ja tā nav, atzīmējam serveri serveru sarakstā, poga **"Rediģēt (Edit)"**, lai labotu informāciju.

\boxtimes	🔀 janis.paraudzins@lu.lv	🛱 Settings 🛛 🗙 🗙	Account Settings A	×		- 🗆	×
	ianis.paraudzins@lu.lv Image: Server Settings Copies & Folders Copies & Folders Copies & Folders Image: Synchronization & Addressing Junk Settings Synchronization & Storage End-To-End Encryption Return Receipts V Image: Disk Space Disk Space Image: Outgoing Server (SMTP) Image: Small Addressing	Settings × Outgoing Server (St When managing your ident can use the default server f Office365 (Microsoft) - s	Account Settings MTP) Settings ities you can use a server fro rom this list by selecting "Use smtp.office365.com (Defaul	x m this li e Defaul t)	st by selecting it as the Outgoing Serve t Server".	r (SMTP), or y Add Edit Remove Set Defau	x you
* 🕸	<u>A</u> ccount Actions 〜 録 Thunderbird Settings 録 Add-ons and Themes ((*)) janis.paraudzins@lu.lv Downloading r	Details of selected serve Description: C Server Name: s Port: 5 User Name: ja Authentication method: C Connection Security: S	er: office365 (Microsoft) mtp.office365.com 87 anpar@edu.lu.lv DAuth2 TARTTLS				

Izejošā servera (SMTP) iestatījumu izvēle

Salīdziniet informāciju, kas ir norādīta attēlā, ja nesakrīt, nomainiet informāciju un noklikšķiniet uz pogas "Labi (OK)".

SMTP Server						
Settings						
Description: Office	Description: Office365 (Microsoft)					
Server Name: smtp.	office365.com					
<u>P</u> ort: 58	Default:587					
Security and Authentication						
Connection security:	STARTTLS 🗸					
Authent <u>i</u> cation metho	d: OAuth2 🗸					
User Na <u>m</u> e:	janpar@edu.lu.lv					
	ОК Cancel					

Izejošā servera (SMTP) iestatījumu logs